

IDEAL FOR REMOVING CARPET AND PLASTER, SCABBLING NATURAL STONE, CHISELLING OUT JOINTS AND POINTING MASONRY

This is the ideal tool for the Construction and Marine industries. It can easily remove tiles and parquet, concrete residues or to peel off heavy coatings.

You will always find the right Von Arx-Chisel Hammer to handle every job.

Available with different chisels.



Chisel hammers • 23 B



Packaging



475×360×110 mm / 18.7×14.1×4.3" Case size

4/5×360	×110 mm	/ 18./×	14.1×4

One case contains	
23 B chisel hammer	
Hose connection G3/8 × 10mm	
Allen key hexagonal	
Tube of grease	
Operating manual	

23	B
700314	

Key features	
Air consumption	100 L/Min., 3.5 cfm
Max. permitted air pres- sure	7 bar, 100 psi
Vibration value on handle	18.70 m/s ²
Sound pressure level	≤ 98.2 db(A)
Acoustic power level	≤ 106.2 db(A)

Field of application

Ideal for removing carpet and plaster, scabbling natural stone, chiselling out joints and pointing masonry. Avail-able with different chisels.

Physical parameters		
Weight	2.0 kg / 4.4 lbs	
Connection thread	G 3/8"	

Recommended lubricants	
BP	Energol RD-E46
Mobil	Almo Oil 325
Shell	Torcula 100
DEA	Arkas 32
Техасо	Aries 32
Esso	Arox EP 46 or EP 100



Packaging



475×360×110 mm / 18.7×14.1×4.3" Case size

One case contains
23 BG chisel hammer
Hose connection G3/8 × 10mm
Allen key hexagonal
Tube of grease
Operating manual



23 BG 700441

Key features

Air consumption	100 L/Min., 3.5 cfm
Max. permitted air pressure	7 bar, 100 psi
Vibration value on handle	16.40 m/s ²
Sound pressure level	≤ 98.2 db(A)
Acoustic power level	≤ 106.2 db(A)

Field of application

Ideal for removing carpet and plaster, scabbling natural stone, chiselling out joints and pointing masonry. Available with different chisels.

Physical parameters		
Weight	1.7 kg / 3.7 lbs	
Connection thread	G 3/8"	

Recommended lubricants	
BP	Energol RD-E46
Mobil	Almo Oil 325
Shell	Torcula 100
DEA	Arkas 32
Техасо	Aries 32
Esso	Arox EP 46 or EP 100



Chisel hammers • 34 B

34 B

700366



Packaging



Case size 475×360×110 mm / 18.7×14.1×4.3" One case contains 34 B chisel hammer

Auxiliary handle

Hose connection G3/8 × 10 mm

Allen key hexagonal Tube of grease Operating manual

Key features	
Air consumption	125 L/Min, 4.4 cfm
Max. permitted air pressure	7 bar, 100 psi
Vibration value on handle	17.10 m/s ²
Sound pressure level	≤ 98.2 db(A)
Acoustic power level	≤ 106.2 db(A)

Field of application

Ideal for removing carpet and plaster, scabbling natural stone, chiselling out joints and pointing masonry. Available with different chisels.

Physical parameters		
2.4 kg / 5.3 lbs		
G 3/8"		
Recommended lubricants		

BP	Energol RD-E46
Mobil	Almo Oil 325
Shell	Torcula 100
DEA	Arkas 32
Техасо	Aries 32
Esso	Arox EP 46 or EP 100



Physical parameters	;
Weight	700464 - 5.8 kg / 12.8 lbs 700343 - 4.0 kg / 8.8 lbs
Lenght	700464 - 160 mm / 6.3" 700343 - 80 mm / 3.1"
Connection thread	G 3/8"





Key features	
Air consumption	125 L/Min, 4.4 cfm
Max. permitted air pressure	7 bar, 100 psi
Vibration value on handle	11.40 m/s ²
Sound pressure level	< 98.2 db(A)
Acoustic power level	< 106.2 db(A)

Field of application

Ideal for removing carpet and plaster, scabbling natural stone, chiselling out joints and pointing masonry. Available with different chisels.

Recommended lubricants	
BP	Energol RD-E46
Mobil	Almo Oil 325
Shell	Torcula 100
DEA	Arkas 32
Техасо	Aries 32
Esso	Arox EP 46 or EP 100



Product catalogue 2022

Chisel hammers • MH 23

MH 23

700738



Packaging



475×360×110 mm / 18.7×14.1×4.3" Case size

One case contains
MH 23 chisel hammer
Hose connection G3/8 × 10 mm
Auxiliary handle
Allen key hexagonal
Tube of grease
Operating manual

Key features	
Air consumption	100 L/Min., 3.5 cfm
Max. permitted air pres- sure	7 bar, 100 psi
Vibration value on handle	9.07 m/s ²
Sound pressure level	≤ 98.2 db(A)
Acoustic power level	≤ 106.2 db(A)

Field of application

Ideal for removing carpet and plaster, scabbling natural stone, chiselling out joints and pointing masonry. Available with different chisels.

Physical parameters	
Weight	2.4 kg / 5.3 lbs
Connection thread	G 3/8"

Energol RD-E46
Almo Oil 325
Torcula 100
Arkas 32
Aries 32
Arox EP 46 or EP 100



Packaging







MH 23 K 706092

Key features

Air consumption	100 L/Min., 3.5 cfm
Max. permitted air pres- sure	7 bar, 100 psi

Vibration value on handle

Sound pressure level

Acoustic power level

Field of application

Ideal for removing carpet and plaster, scabbling natural stone, chiselling out joints and pointing masonry. Available with different chisels.

12.79 m/s²

≤ 98.2 db(A)

≤ 106.2 db(A)

Physical parameters	
Weight	2.3 kg / 5.1 lbs
Connection thread	G 1/4"

Recommended lubricants	
BP	Energol RD-E46
Mobil	Almo Oil 325
Shell	Torcula 100
DEA	Arkas 32
Техасо	Aries 32
Esso	Arox EP 46 or EP 100



45B

700409



Packaging



Case size

475×360×110 mm / 18.7×14.1×4.3"

One case contains	
45 B needle scaler	
Hose connection G3/8 × 10 mm	
Auxiliary handle	
Tube of grease	
Operating manual	

Key features Needles ø 3 mm 49 pcs. pointed Air consumption 158 L/Min, 5.6 cfm Max. permitted air pressure 7 bar, 100 psi Vibration value on handle 20.90 m/s²

≤ 100.7 db(A)

≤ 110.0 db(A)

Field of application

Sound pressure level

Acoustic power level

The unit is intended for machining the surfaces of metal, concrete and stone for the purposes of cleaning, derusting, roughening, descaling, clearing, smoothing and bush-hammering.

Physical parameters		
Weight	4.8 kg / 10.6 lbs	
Connection thread	G 3/8"	

Recommended lubricants	
BP	Energol RD-E46
Mobil	Almo Oil 325
Shell	Torcula 100
DEA	Arkas 32
Техасо	Aries 32
Esso	Arox EP 46 or EP 100



		Recommended lubricants	
		BP	Energol RD-E46
		Mobil	Almo Oil 325
		Shell	Torcula 100
Physical parameters	\$	DEA	Arkas 32
Weight	9.4 kg / 20.7 lbs	Техасо	Aries 32
Length	1800 mm / 71"	Esso	Arox EP 46 or EP 100





49 pcs. pointed

7 bar, 100 psi

16.20 m/s²

≤ 100.7 db(A)

≤ 110.0 db(A)

158 L/Min, 5.6 cfm

Key features

Needles ø 3mm

Air consumption

Max. permitted air pressure

Vibration value on handle

Sound pressure level

Acoustic power level

Field of application

The unit is intended for machining the surfaces of metal, concrete and stone for the purposes of cleaning, derusting, roughening, descaling, clearing, smoothing and bush-hammering.







Packaging



475×360×110 mm / 18.7×14.1×4.3" Case size

One box contains	R
MH 34 chisel hammer	BF
Hose connection G3/8 × 10 mm	М
Auxiliary handle	Sł
Allen key hexagonal	DI
Tube of grease	Te
Operating manual	Es

Key features	
Air consumption	125 L/Min., 4.4 cfm
Max. permitted air pressure	7 bar, 100 psi
Vibration value on handle	10.29 m/s ²
Sound pressure level	≤ 98.2 db(A)
Acoustic power level	≤ 106.2 db(A)

Field of application

Ideal for removing carpet and plaster, scabbling natural stone, chiselling out joints and pointing masonry. Available with different chisels.

Physical parameters		
Weight	2.8 kg / 6.2 lbs	
Connection thread	G 3/8"	

Recommended lubricants	
BP	Energol RD-E46
Mobil	Almo Oil 325
Shell	Torcula 100
DEA	Arkas 32
Техасо	Aries 32
Esso	Arox EP 46 or EP 100



	Recommended lubricants		
	BP	Energol RD-E46	
		Mobil	Almo Oil 325
Physical parameters		Shell	Torcula 100
Weight	8.0 kg / 17.6 lbs	DEA	Arkas 32
Lenght	1350 mm / 53"	Техасо	Aries 32
Connection thread	G 3/8"	Esso	Arox EP 46 or EP 100





Key features

Air consumption	158 L/Min, 5,6 cfm
Max. permitted air pres- sure	7 bar, 100 psi
Vibration value on handle	17.10 m/s ²
Sound pressure level	≤ 98.2 db(A)
Acoustic power level	≤ 106.2 db(A)

Field of application

Ideal for removing carpet and plaster, scabbling natural stone, chiselling out joints and pointing masonry. Available with different chisels.

Product catalogue 2022

SPARE PARTS



www.vonarx.com

YOU WILL ALWAYS FIND THE **RIGHT TOOL TO HANDLE EVERY JOB.**

Learn more about our products on www.VONARX.com



VON ARX EOOD

20, Nedyalka Shileva street South Industrial zone Trakiya 4000, Plovdiv Bulgaria Phone: +359 32 940553 E-mail: order@vonarx.com E-mail: info@vonarx.com

